

ACCESSORIES AND OPTIONS

OPTIONS:

A	= Stainless steel version (pag. 89)
AA	= Industry version (pag. 90)
B	= Bellows boot (pag. 87)
CG	= Bellflange with coupling (on request)
E	= Viton seals (pag. 89)
FX	= Anticorrosion painting (pag. 90)
FXC	= Cataphoresis (pag. 90)
G	= Safety nut (pag. 87)
H	= Handwheel (pag. 88)
L	= Anti rotation device (pag. 85)
MM	= Manual driving for ALI1 and ALI1-P models (pag.89)
N	= Manual driving with safety limit switch (pag.88)
O	= Body integrated Swivelling shafts (on request)
OA	= Front Swivelling plate (on request)
OP	= Rear Swivelling plate (on request)
P	= Handwheel and safety-switch (pag. 88)
PO	= Rear-pipe for swinging movement (on request)
S	= Torque limiter (pag.85)
T	= Additional shaft (pag.86)
Z	= Low noise (pag. 89)

N. DIS. = Drawing number: Request of no standard options.

ACCORDING TO THE OPTIONS DESIRED, ADD THE IDENTIFICATION LETTERS AT THE END OF THE ORDERING KEY RELATED TO THE PRODUCT CHOSEN

Examples:

ALI5 / 0300 / M01 / CA-400-50-T-71-2-0,55 / B5+AB / M1-FC1 / 1 / E05 / 2FC0 / POT01A / P1 / A1

Ordering key for
standard product

ALI5 / 0300 / M01 / CA-400-50-T-71-2-0,55 / B5+AB / M1-FC1 / 1 / E05 / 2FC0 / POT01A / P1 / A1 + AA + S + T

Ordering key for
standard product + options

ALI5 / 0300 / M01 / CA-400-50-T-71-2-0,55 / B5+AB / M1-FC1 / 1 / E05 / 2FC0 / POT01A / P1 / A1 / S + T / N.DIS

Ordering key with NO
standard options